

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61B 19/00, 17/34	A1	(11) International Publication Number: WO 99/29250 (43) International Publication Date: 17 June 1999 (17.06.99)
(21) International Application Number: PCT/US98/25844 (22) International Filing Date: 4 December 1998 (04.12.98) (30) Priority Data: 08/990,572 11 December 1997 (11.12.97) US (71) Applicant: SMITH & NEPHEW, INC. [US/US]; 1450 Brooks Road, Memphis, TN 38116 (US). (72) Inventor: LUCEY, Paul, V.; 3 Colleen Drive, Salem, NH 03079 (US). (74) Agents: STACEY, George, K. et al.; Smith & Nephew, Inc., 1450 Brooks Road, Memphis, TN 38116 (US).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: LAPAROSCOPIC ACCESS PORT WITH CONTROLLED SEALING VALVE



(57) Abstract

In laparoscopic surgery or the like, access is provided to an opening in a body cavity that contains insufflation gas at an insufflation pressure. The flow of insufflation gas from the body cavity through the opening is limited in response to the sensed insufflation pressure in the cavity.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

LAPAROSCOPIC ACCESS PORT WITH CONTROLLED SEALING VALVE

The invention relates to methods and apparatus for providing
5 access to a body cavity of a patient during surgery.

In some forms of surgery, such as laparoscopy, a surgeon
operates on a patient through one or more incisions that provide
access to a patient's body cavity. The surgeon inserts through the
10 incisions one or a combination of surgical implements, including
visual aid devices such as a laparoscope or endoscope, the
surgeon's hand or hands, and surgical instruments for, e.g.,
grasping, cutting, or grinding tissue. The body cavity is inflated with
an insufflation gas to facilitate access to one or more organs or
15 surgical sites.

In one aspect of the invention, there is provided an apparatus
for providing access to an opening in a body cavity containing
insufflation gas at an insufflation pressure, the apparatus comprising
20 a controllable valve defining an access channel in fluid
communication with the opening, the valve being responsive to an
actuation signal to restrict flow of insufflation gas from the body
cavity through the opening; a sensor for providing an output signal
corresponding to the insufflation pressure; and a controller
25 responsive to the output signal provided by the sensor to provide the
actuation signal to the controllable valve.

In this embodiment, the apparatus including a controllable
valve provides access to an opening in a body cavity containing
30 insufflation gas at an insufflation pressure. A controller responsive
to a pressure sensor output signal corresponding to the insufflation
pressure provides an actuation signal, to which the controllable

valve responds to restrict flow of insufflation gas from the body cavity through the opening.

Embodiments of this aspect of the invention can include one
5 or more of the following features. The controllable valve, which can include an inflatable annular bladder sized to fit within the opening, is actuated to restrict flow (e.g., by inflating the bladder) when the insufflation pressure is below a desired level. The bladder can have a conical shape, with the smaller end arranged closer to the opening
10 in the body cavity than the larger end, and can also be segmented. The controllable valve can be an iris valve. The output signal from the sensor can be an electrical signal, or can be a mechanical signal provided by, e.g., an arm, lever, or diaphragm that moves in response to insufflation pressure.

15

In another aspect of the invention, a system for providing access to a body opening in a body cavity containing insufflation gas includes an inflatable annular bladder. The body opening can be accessed through the central opening defined by the annular
20 bladder. In response to a pressure sensor output signal corresponding to the insufflation pressure, a controller controls a source of pressurized gas to provide pressurized gas to the bladder chamber.

25 Embodiments of this aspect of the invention can include one or more of the following features. The controller controls the source of pressurized gas to provide pressurized gas to the bladder chamber when the insufflation pressure is below a predetermined level (e.g., as indicated by a sensor in fluid communication with the
30 chamber). No pressurized gas is provided to the bladder when the insufflation pressure is above the predetermined level.

Another source of pressurized gas is also in selective fluid communication with the body cavity. The controller can control this source of gas to provide pressurized gas to the body cavity when
5 the insufflation pressure is below the predetermined level, and to not provide pressurized gas to the body cavity when the insufflation pressure is above the predetermined level.

In another aspect of the invention, access is provided to an
10 opening in a body cavity that contains insufflation gas at an insufflation pressure. The flow of insufflation gas from the body cavity through the opening is limited in response to the sensed insufflation pressure being below a predetermined level.

Embodiments of this aspect of the invention can include one
15 or more of the following features. Flow of insufflation gas from the body cavity through the opening can be limited by inflating an inflatable annular bladder in a tube positioned in or around the opening, e.g., to a pressure that is a function of the insufflation
20 pressure. The bladder is inflated, and insufflation gas is supplied to the body cavity, when the sensed insufflation pressure is below the predetermined level. The bladder is at least partially deflated when the sensed insufflation pressure is above the predetermined level. In this deflated or partially deflated state, the bladder can passively
25 limit the flow of insufflation gas from the body cavity through the opening.

In another aspect of the invention, an apparatus for providing
access to a body opening in a body cavity containing insufflation gas
30 includes an inflatable bladder carried in a housing. The housing has opposed open ends and a passageway through which one or more

4

surgical implements can be inserted. The bladder fits inside the housing and is configured to receive fluid at a pressure that is a function of the insufflation pressure.

- 5 Embodiments of this aspect of the invention can include one or more of the following features. The bladder can be conical, annular, segmented, or sized to fit within the body opening.

10 The invention provides a variety of advantages, including guarding against the loss of insufflation pressure in the body cavity during laparoscopic surgery or the like. The valve can be operated in accordance with the insufflation pressure. The valve need not be fully "open" or fully "closed," but rather can be operated over a range of values in accordance with insufflation pressure to reduce the
15 degree to which the valve limits the surgeon's ability to access the body cavity. Insufflation pressure may be maintained even when implements are inserted and removed from the valve at relatively high frequency.

- 20 Other advantages and features will become apparent from the following description, as well as from the claims.

FIG. 1 is a schematic view of an insufflation system.

- 25 FIG. 2 is a partially cross-sectional view of a valve assembly for use in the system shown in FIG. 1.

FIG. 3 is a partially cross-sectional detail view of the system shown in FIG. 1.

FIG. 4 is a graph showing bladder pressure versus insufflation pressure.

- 30 FIG. 5 is a partially cross-sectional view of another valve assembly for use in the system shown in FIG. 1.

FIGS. 6-7 are partially cross-sectional detail views of insufflation systems.

As shown in FIG. 1, an insufflation system 10 is used to
5 insufflate a body cavity 11 in the area of an incision 13 in a patient 12. The system 10 includes a valve assembly 14, a valve pump 16, a controller 18, an insufflation pump 20, and an insufflation needle 22. The controller 18 controls the valve pump 16 to provide pressurized air to the valve assembly 14, as described in detail
10 below. The controller 18 also controls the insufflation pump 20 to regulate the insufflation pressure in the body cavity 11. The insufflation pump 20 (e.g., a Dyonics Laparoscopic Insufflator Model No. 7205362) can supply pressures sufficient to insufflate the body cavity 11. For example, the insufflation pump 20 can inflate the
15 body cavity 11 to approximately 50 mm Hg (2 in. Hg), while a typical insufflation pressure is 15 mm Hg (0.6 in. Hg). A signal representing the insufflation pressure is provided by an insufflation pressure sensor 72 and sent to the controller 18. The controller 18 can be any device capable of sending control signals to control the
20 insufflation pump 20 and the valve pump 16, e.g., a personal computer or a dedicated microprocessor and associated circuitry. Typically, the controller 18 is programmed using software, hardware, firmware, hardwiring, or a combination of any of these. A surgeon can access the body cavity 11 through the valve assembly 14, e.g.,
25 to insert an implement into the cavity.

As shown in FIG. 2, the valve assembly 14 includes a bladder 23 carried in a rigid tube 24 attached to a sleeve 38. The sleeve 38 is flexible and sized to fit over the surgeon's forearm. The proximal
30 end 42 of the sleeve 38 includes, for example, a hook and loop fastener strap that can be secured around the surgeon's arm to

guard against loss of insufflation gas. The sleeve 38 connects to a sleeve coupling 40 that releasably connects to the tube 24 using a releasable coupling such as disclosed in U.S. Patent No. 5,653,705 (issued August 5, 1997 to De La Torre) incorporated by reference
5 herein. A circular inside surface 26 of the tube 24 forms a seal, preferably air-tight, with an outer perimeter 25 of the bladder 23. The bladder 23 fits snugly within, and is bonded to, the tube 24. The bladder 23 can be sealed to the tube 24 by, e.g., an adhesive, heat welding, or inflating the bladder 23 to expand and conform it to
10 the inside surface 26 of the tube 24 with an interference fit. Also, the bladder 23 can be carried by a rigid or semi-rigid member that is slid into the tube 24 and mounted at an appropriate location. The bladder-and-member assembly can be removed, e.g., for replacement when it becomes worn or soiled.

15

The tube 24 is sized to allow access to the body cavity 11 (FIG. 1) through an opening 28 defined by the bladder 23 along the direction indicated by arrows 30. For example, the tube 24 can be sized to allow insertion of the surgeon's hand and/or forearm
20 through the opening 28, in which case the inside surface 26 can have a diameter on the order of 100 mm (4 in.). For inserting smaller implements such as endoscopes or surgical instruments, the tube can be smaller, e.g., with an inside diameter on the order of 5-10 mm (0.2-0.4 in.).

25

The tube 24 has a distal section adapted to be mounted to the patient 12. As shown, the distal section includes a flange 44 that can be mounted directly to the patient using an adhesive, by suturing, or by other appropriate means.

30

The bladder 23 is inflatable, conical and annular. The bladder 23 is preferably flexible enough that an inner surface of the bladder 23 conforms to the periphery of the implement, yet is durable enough to resist puncture or rupture in normal use. For example, the bladder 23 can be made of a flexible polymer, such as polypropylene or latex. The maximum intended operating pressure of the bladder 23 depends on a variety of factors such as the bladder material, the amount that the surgeon needs to manipulate the implement inside the opening 28, and the bladder's shape. The conical shape of the bladder 23 allows it to conform, either actively under control of the controller 18 or passively due to, e.g., the insufflation pressure, to the implement. The conical shape also facilitates insertion of implements through the opening 28, while guarding against the bladder 23 turning upwards, and thus allowing insufflation gas in the body cavity 11 to escape, when the surgeon removes the implement. Either or both the bladder 23 and the implement can be lubricated to facilitate insertion and removal of the implement.

The valve pump 16 (e.g., an ACI Medical Model No. 025.20-12) is connected to the bladder 23 by a valve pump gas line 52. The bladder 23 conforms to the implement as the valve pump pressurizes the bladder 23. The valve pump 16 can pressurize the bladder 23, e.g., up to 200 mm Hg, and can release gas from the bladder 23 to reduce the pressure in the bladder 23 to as low as 0 mm Hg. The pressure in the bladder 23 is monitored by a bladder pressure sensor 74, in the valve pump 16, that sends a signal representative of the bladder pressure to the controller 18. If the bladder pressure exceeds the maximum desired pressure for the bladder 23, then the valve pump 16, either on its own or under direction of the controller, can shut off, reduce output, or provide

either or both of a visual or audio warning. The valve pump 16 also has a manual shutoff switch 70. The valve pump 16 can be a multichannel pump as shown in FIG. 3.

5 As shown in FIG. 3, if the valve pump 16 is a multichannel pump (i.e., it can provide multiple independent pressures to, and sense multiple independent pressures in, multiple valves), then two valve assemblies 14a, 14b similar to valve assembly 14 can be used together in a surgical procedure. Alternatively, separate valve
10 pumps 16, one for each valve, can be used. Signals representing bladder pressures are provided by bladder pressure sensors 74a, 74b to the controller 18. The valve 14a is sized for insertion of the surgeon's hand (not shown) and the valve 14b is sized to receive an implement such as a surgical instrument or a visual aid device (not
15 shown).

 In a surgical procedure, the valve assemblies 14a, 14b are attached to the patient 12 so that they are sealed in or around the incision 13. For instance, the valve assembly 14a is attached
20 around the incision 13 and the valve assembly 14b is inserted through a body wall 50 of the patient 12 directly into the body cavity 11. The valve pump 16 is connected to the bladders 23a, 23b through respective valve pump gas lines 52a, 52b. The insufflation
25 needle 22 is inserted through the body wall 50, and an insufflation pump gas line 54 connects the insufflation needle 22 to the insufflation pump 20. The valve pump gas lines 52a, 52b and the insufflation pump gas line 54 are preferably flexible, and made of a material that can withstand the pressures encountered during use. Electrical lines 56 and 58 connect the controller 18 to the valve
30 pump 16 and the insufflation pump 20, respectively, and provide bi-

directional communication between the pumps and the controller 18 for the pressure and control signals.

During the procedure, the controller 18 actively controls the
5 insufflation pump 20 and the valve pump 16 to maintain sufficient
insufflation pressure inside the body cavity 11. Insufflation pressure
may drop due to, among other things, leaks in or around the
insufflation needle 22, the tubes 24a, 24b, or in the openings 28a,
28b. Insufflation gas can also escape when the endoscope is
10 removed, e.g., to clean off condensation or body fluids. The
controller 18 can control the valves to allow insufflation gas to
escape from the body cavity 11.

Referring to FIG. 4, when the insufflation pressure is at or
above a desired insufflation pressure IP_1 , the bladders in the valves
15 are pressurized to BP_1 , typically 1-2 mm Hg (0.04-0.08 in. Hg), with
the valve pump 16 releasing gas from the bladder 23 as necessary.
Should the insufflation pressure drop below IP_1 , the controller 18
signals the valve pump 16 to pressurize the bladders and the
insufflation pump 20 to pressurize the cavity. As the insufflation
20 pressure drops below the desired pressure IP_1 , the valve pump 16
linearly increases the bladder pressures until the maximum bladder
pressure BP_{max} is reached. Insufflation gas is supplied as
necessary to the body cavity. The surgeon can also adjust the
bladder pressure, e.g., so that he can more easily manipulate the
25 implement.

Other embodiments are within the scope of the claims.

For example, FIG. 5 shows an alternative valve assembly 76
including a sectional bladder 78 that has several triangular-shaped
bladder segments or wedges 34. The bladder segments 34 may be
30 fed by a single valve pump line 36 from the valve pump 16.
Alternatively, the sectional bladder 78 may be a single piece with an

undivided peripheral portion and a segmented central portion. Other bladder segment shapes could instead be used, such as rectangles or wedges with flattened or concave ends, as opposed to pointed ends. Also, the perimeter 79 of the sectional bladder 78 (or the
5 perimeter 25 of the bladder 23) may be elliptical, rectangular, or square, with the inside surface 26 of the tube 24 having a similar shape.

The bladder 23 does not have to be annular. For example,
10 the bladder can be a spherical balloon with no opening, carried on one side of the inner wall of the tube 24. As the bladder inflates, it presses the surgical implement against the opposite wall, and forms a seal around it.

15 Regardless of shape or configuration, the bladder 23 can be inflated with, and the valve pump 16 can supply, any fluid capable of pressurizing the bladder, such as a liquid (e.g., saline).

The tube 24 and sleeve coupling 40 can take a variety of
20 forms. The tube 24 can be flexible or semi-rigid. All or part of the tube 24 can be pleated, giving the tube an accordion shape. The distal section of the tube 24 can include a threaded end 46 to be screwed into a mating coupling or other device (not shown) that seals to the patient 12 in or around the incision 13 (FIG. 1). The
25 sleeve coupling 40 can be adapted to have the sleeve 38 clipped, snapped, or tied to the sleeve coupling 40.

The relationship between insufflation pressure and bladder
pressure does not have to be the linear relationship shown in FIG. 4.
30 For example, the bladder pressure could be a step response as a function of the insufflation pressure, rising quickly from BP_1 to the

maximum bladder pressure when the insufflation pressure drops below IP_1 .

FIG. 6 illustrates another embodiment of a valve assembly 80 that can be used at or near the incision 13. A sealing device 60 retracts the incision 13 and supports a bladder 82, which can be similar to the bladder 23 of FIG. 2 or the sectional bladder 78 of FIG. 5. The sealing device 60 can be an inflatable annular bladder, or can be rigid. The tube 24 (FIGS. 2, 5) can be configured to include the sealing device 60.

FIG. 7 illustrates another embodiment of a valve assembly 84, in which an iris shutter 86 can be used to close off a tube 88. A lower ring 66 is fixedly attached to the tube 88. A motor 62 actuates an upper ring 64 of the iris shutter 86, causing a flexible sheath 68 to twist and conform to the implement. While the iris shutter 86 is shown as being displaced a distance away from the patient 12, the iris shutter 86 may also be used at the level of the incision 13.

12
CLAIMS

1. An apparatus for providing access to an opening in a body cavity containing insufflation gas at an insufflation pressure, the apparatus comprising:
- a controllable valve defining an access channel in fluid communication with the opening, the valve being responsive to an actuation signal to restrict flow of insufflation gas from the body cavity through the opening;
- a sensor for providing an output signal corresponding to the insufflation pressure; and
- a controller responsive to the output signal provided by the sensor to provide the actuation signal to the controllable valve.
2. The device of claim 1 wherein the controller produces the actuation signal if the output signal is indicative of an insufflation pressure below a desired insufflation pressure.
3. The device of claim 1 wherein the controllable valve comprises an inflatable bladder.
4. The device of claim 3 wherein the inflatable bladder is annular.
5. The device of claim 4 wherein the inflatable annular bladder has a conical shape.
6. The device of claim 4 wherein the inflatable annular bladder is segmented.

7. The device of claim 4 wherein the annular bladder is sized to fit within the opening.
8. The device of claim 1 wherein the controllable valve
5 comprises an iris valve.
9. The device of claim 1 wherein the output signal is electrical.
10. A system for providing access to an opening in an area of a
10 body cavity containing insufflation gas at an insufflation pressure, the apparatus comprising:
an inflatable annular bladder defining a chamber and a
bladder opening through which the body opening can be accessed;
a first source of pressurized gas in selective fluid
15 communication with the chamber;
an insufflation pressure sensor for providing an output signal corresponding to the insufflation pressure; and
a controller responsive to the output signal provided by the
insufflation pressure sensor for providing a first control signal to
20 control the first source to provide pressurized gas to the chamber.
11. The system of claim 10 wherein the controller provides the first control signal if the output signal indicates an insufflation pressure below a predetermined insufflation pressure.
- 25
12. The system of claim 10 wherein the controller does not provide the first control signal if the output signal indicate an insufflation pressure above a predetermined pressure.

13. The system of claim 10 further comprising a second source of pressurized gas in selective fluid communication with the body cavity, wherein the controller is responsive to the output signal provided by the insufflation pressure sensor for providing a second control signal to control the second source to provide pressurized gas to the body cavity if the output signal indicates an insufflation pressure below a predetermined insufflation pressure.


14. The system of claim 10 further comprising a second source of pressurized gas in selective fluid communication with the body cavity, wherein the controller is responsive to the output signal provided by the insufflation pressure sensor to provide a second control signal to control the second source not to provide pressurized gas to the body cavity if the output signal indicates an insufflation pressure above a predetermined insufflation pressure.



15. The system of claim 10 further comprising:
a chamber pressure sensor for providing a chamber pressure signal corresponding to a pressure in the chamber of the bladder;
an indicator responsive to the output signal of the insufflation pressure sensor and to the chamber pressure signal for providing an indication that the chamber pressure has reached a predetermined chamber pressure while the insufflation pressure is below a predetermined insufflation pressure.

16. A method comprising:
providing access to an opening in a body cavity containing
insufflation gas at an insufflation pressure;
sensing the insufflation pressure; and
5 limiting flow of insufflation gas from the body cavity through
the opening in response to the sensed insufflation pressure being
below a predetermined level.
17. The method of claim 16 further comprising facilitating flow of
10 insufflation gas from the body cavity through the opening in
response to the insufflation pressure being above the predetermined
level.
18. The method of claim 16 further comprising the step of
15 passively limiting the insufflation gas flow from the body cavity
through the opening.
19. The method of claim 16 wherein the limiting step comprises
inflating an inflatable annular bladder.
20
20. The method of claim 19 wherein the inflating step comprises
inflating the bladder such that a pressure inside the bladder is a
function of the insufflation pressure.
21. The method of claim 19 further comprising at least partially
25 deflating the bladder in response to the sensed insufflation pressure
being above the predetermined level.
22. The method of claim 16 further comprising the step of
30 supplying insufflation gas to the body cavity in response to the
sensed insufflation pressure being below the predetermined level.

23. An apparatus for providing access to a body opening in a body cavity containing insufflation gas at an insufflation pressure, the apparatus comprising:
- 5 a housing defining a passageway sized and configured to receive one or more surgical implements, the housing having open opposed first and second ends; and
- an inflatable bladder carried inside the housing intermediate the opposed first and second ends, the inflatable bladder being
- 10 configured to receive fluid under pressure, wherein the pressure of the received fluid is a function of the insufflation pressure.
24. The apparatus of claim 23 wherein the bladder is annular and defines a bladder opening through which the body opening can be
- 15 accessed.
25. The apparatus of claim 24 wherein the bladder has a conical shape.
- 20 26. The apparatus of claim 23 wherein the bladder is segmented.
27. The apparatus of claim 23 wherein the bladder is sized to fit within the body opening.


1/5







3/5

FIG. 3.




4/5



5/5

FIG. 7.



INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/US 98/25844

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61B19/00 A61B17/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	EP 0 807 416 A (GAYA LTD) 19 November 1997 see column 3, line 4-9 see column 5, line 56 - column 6, line 4 see column 7, line 3 - line 22 -----	23-27 1,10
A	US 5 640 977 A (LEAHY PATRICK F ET AL) 24 June 1997 see column 2, line 3 - line 5 see column 5, line 36 - line 40 -----	23

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *S* document member of the same patent family

Date of the actual completion of the international search

24 March 1999

Date of mailing of the international search report

31/03/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5618 Patentsaan 2
NL - 2280 HV Rijswijk
Tel: (+31-70) 340-2040, Tx: 31 651 epo nl
Fax: (+31-70) 340-3018

Authorized officer

Gérard, B

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 98/ 25844

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 16-22
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1 (iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/25844

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 807416 A	19-11-1997	IE 940150 A	04-10-1995
		IE 940613 A	04-10-1995
		IE 950055 A	07-08-1996
		AT 164303 T	15-04-1998
		AU 695770 B	20-08-1998
		AU 1717395 A	04-09-1995
		BR 9506817 A	09-09-1997
		CA 2183064 A	24-08-1995
		CN 1144471 A	05-03-1997
		CZ 9602404 A	16-04-1997
		DE 69501880 D	30-04-1998
		DE 69501880 T	23-07-1998
		EP 0744922 A	04-12-1996
		ES 2115365 T	16-06-1998
		FI 963226 A	17-10-1996
		HU 76016 A	30-06-1997
		WO 9522289 A	24-08-1995
		JP 9509079 T	16-09-1997
		NO 963421 A	14-10-1996
		NZ 279907 A	26-06-1998
		PL 315939 A	09-12-1996
		US 5803921 A	08-09-1998
		ZA 9501378 A	24-10-1995
US 5640977 A	24-06-1997	AU 2223195 A	30-10-1995
		AU 2240395 A	30-10-1995
		IE 71634 B	26-02-1997
		WO 9527445 A	19-10-1995
		WO 9527468 A	19-10-1995